



WWW.FLASHLIGHT.COM

Engineering Data Sheet : 200301

Unit Information

2 AA-Cell Submersible Pocketlight in Orange
Model #: 200301
UPC-IC : 1673120301 (orange)
1673120302 (yellow)
1673120303 (black)

Master Pack Dimensions

Weight: 3 lbs.
Cube: 1.03 ft³ (.03 m³)
Cube Dimensions: 10.06" x 5.625" x 10.5"
Quantity: 12 pcs.

Specifications

Power Source: 2 AA Cell
Bulb/Lamp: Xenon
Bulb/Lamp Life: 15 Hours
Light Output: 13,000 Beam Candlepower
Weight (Without batteries): 2.2 oz.
Replacement Bulb: XPR2AA
Approximate Burn time during continuous use:
3 hours 30 min.
Approximate Burn time during intermittent use:
4 hours 30 min

Components

Lens: Polycarbonate with Thermoplastic Elastomer (TPE)
Reflector: Ultem 1000
Tube: Super Tough Nylon
Contact Strip: Spring Brass
Switch Boot: Thermoplastic Elastomer (TPE)

Product Features

- UL Division 1 & 2 Listed
- Non-Conductive
- Passes 30 foot drop onto concrete
- 13,000 Candle Power
- Pushbutton Switch
- Pre-focused spot beam
- Key Ring
- Lifetime Limited Warranty
- Xenon Bulb
- Submersible to 100ft
- Pocket size
- Fits Helmet Clips

Unit Dimensions

Length: 6.65"
Width: 1.42"
Height: 1.4



Safety Approvals

UL: Class I, Division 1, Group C & D
Class I, Division 2 Group A, B, C, & D
Class II, Division 2, Group G
Operating Temp. Code T3C
CSA: Class I, Division 2, Group A,B,C,D
Class II, Division 2, Group G
Operating Temp. Code T3C
MSHA: Approved for use as mining equipment
ATEX II 2 G EEX ib e IIB T3

Accessories Available

598 Industrial Helmet Clip
585 Over/Under Helmet Clip
597 Belt Holster